

**In the Claims**

1. (Currently Amended) A golf putter head, comprising:

a top, a bottom, [[a]] opposed flat striking surfaces, [[a]] opposed curvilinear striking surfaces and a shaft receiving aperture;

said flat striking surfaces having a first striking line extending parallel to said flat striking surfaces;

a first cylindrical portion and a second cylindrical portion defining said curvilinear striking surfaces, said curvilinear striking surfaces having [[a]] second striking lines at a toe end of said first striking line and at a heel end of said first striking line, each of said second striking lines extending parallel to the axis of said cylindrical portions and substantially perpendicular to said first striking line; and

at least one recess along said bottom disposed between said first and second cylindrical portions; and,

said second striking lines being located at a distance higher from said bottom than said first striking line when said first cylindrical portion and said second cylindrical portion are contacting said substrate.

2. (Currently amended) The golf putter head of claim 1 wherein said curvilinear striking surfaces have[[s]] an interior radius ranging from 0.84 inches to 0.9375 inches.

3. (Withdrawn) The golf putter head of claim 1 wherein said bottom has at least one recessed portion.

4. (Withdrawn) The golf putter head of claim 3 wherein said at least one recessed portion is semicircular having a radius of 0.875 inches.

5. (Original) The golf putter head of claim 1 wherein said top has a concave portion.
6. (Currently Amended) The golf putter head of claim 5 wherein said concave portion has a radius of 0.875 inches to 1.0 inch.
7. (Withdrawn) The golf putter head of claim 1 wherein said flat striking surfaces contains an insert.

Claims 8-10 (Canceled).

11. (Withdrawn) A golf putter head comprising:
  - a top, a bottom, a flat striking surface, a curvilinear striking surface, a shaft receiving aperture;
  - said flat striking surface having a first striking line;
  - said curvilinear striking surface having a second striking line;
  - said second striking line being located at a distance higher from said bottom than said first striking line;
  - said bottom having at least one beveled edge; and
  - said bottom having at least one convex portion.

12. (Withdrawn) The golf putter head of claim 11 wherein said top has at least one convex portion.

13. (Withdrawn) The golf putter head of claim 11 wherein at least one of said curvilinear striking surfaces has an interior radius ranging from 0.8125 inches to 0.9375 inches.

14. (Withdrawn) The golf putter head of claim 11 wherein said flat striking surfaces contains an insert.

Claims 15-19 (Canceled).

20. (Currently amended) A golf putter head, comprising:

a top surface and a bottom surface;

at least one flat surface for striking a golf ball extending between said top and bottom surfaces;

first and second ends connecting said top and bottom surface and said at least one flat surface, said first and second ends being generally cylindrical in shape defining a curvilinear surface and ~~defining~~ at least a second location for striking ~~[[a]]~~ said golf ball;

said at least second striking locations at a toe end of said first striking surface and at a heel end of said first striking surface being perpendicular to said first striking locations;

at least one recess disposed between said first and second cylindrical ends adjacent said bottom surface;

said curvilinear end surfaces each having a radius which is greater than a radius of a golf ball such that a second strike line is higher than a first strike line when said first strike line is parallel to the ground.